


AvediaStream® Gateway

AvediaStream g4417-pi Gateway | avstr-g4417-pi



The AvediaStream g4417-pi Gateway receives content-protected live TV and radio from satellite sources and streams it securely across an IP network. With dual conditional access slots and built-in Pro:Idiom® encryption, the g4417-pi meets the most stringent content protection requirements and delivers high value and broadcaster premium channels across your IP network.

Interfaces

- Two DVB-S/S2 tuners (dual 75 ohm F-type input connectors)
- Two 802.3 10/100/1000BaseT Ethernet (RJ-45 chassis sockets, dual Ethernet features require AvediaStream c1210 chassis)
- Serial RS232 port for local administration (RJ-45 chassis socket)

Streaming

- Single program MPEG-2 transport streams (ISO/IEC 13818-1)
- RTP, UDP
- IP multicast, IP unicast
- Pro:Idiom and Pro:Idiom Media stream encryption
- IGMP Join Group for enhanced switch compatibility
- Streaming output up to 144 Mbps

Channel Management

- Channel announcement via SAP/SDP
- Interoperable with LG hospitality SmartTVs (see conformance certificates for details)
- Configurable DVB-S/S2 scanning (basic and advanced modes)
- Stream specific channels from selected multiplexes
- Multicast/unicast address selection (automatic or manual)
- Configure name, number and group membership per channel
- Fine-grained control over audio, subtitles and other channel metadata using advanced PID filtering:
 - Create custom SPTS streams containing elements from a channel
 - Filters on PSI data, table types and PID number
 - Unlimited number of PIDs filtered

Management

- Configurable using management tools:
 - Admin level management using AvediaServer Site Manager application
 - HTTP/HTTPS device web interface; recommended browser: Chrome®
- SNMP
- RESTful API
- Serial RS232 Admin Port
- Event logging via Syslog (local and remote)
- Firmware upgrade via TFTP
- Configuration backup/restore via TFTP

RF Input

- Input connector: two 75 ohm F-type
- Tuning range: 950 to 2150 MHz
- Input level: -25 dBm to -65 dBm
- Maximum data rate: 72Mbps per transport stream
- LNB supply: 350mA per RF input with short-circuit protection
- LNB voltage: 13 or 18V

Signal Modulation / Coding:

- DVB-S (ETSI EN 300 421 Broadcast services)
 - Modulation: QPSK: 1/2, 2/3, 3/4, 5/6, 7/8
 - Symbol rates: 1 to 45 MSymbols/s
 - FEC: Reed Solomon & Viterbi
 - Roll off: 0.35
- DVB-S2 (ETSI EN 302 307 Broadcast services)
 - Modulation: QPSK: 1/4, 1/3, 2/5, 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10
 - 8PSK: 3/5, 2/3, 3/4, 5/6, 8/9, 9/10
 - Symbol rates: 1 to 45 MSymbols/s
 - FEC: LDPC & BCH
 - Roll off: 0.2, 0.25, 0.35
- DiSEqC: 1.0, 1.1, 1.2

Network

- Linux dual IPv4/IPv6 stack
- DHCP/DHCPv6 or Static IP addressing
- Two IEEE 802.3u 10/100/1000Mbps MDIX Ethernet interfaces
- Ethernet redundancy - automatic switching to secondary Ethernet if network failure occurs (c1210 chassis required)

System

- Linux-based

Protocols

IP (RFC 791), UDP (RFC 768), TCP (RFC 793), ARP (RFC 826), DNS (RFC 1035), DHCP (RFC 2131), ICMP (RFC 792), IGMP v3 (RFC 3376), TFTP (RFC 1350), HTTP (RFC 2616), HTTPS (RFC 2818), Syslog (RFC 3164), NTP (RFC 1305), SAP (RFC 2974), SDP (RFC 4566), RTP (RFC 3550), SNMP (v1, v2c RFC 1901), IPv6 (RFC 8200), SSDP, DHCPv6 (RFC 8415), SLAAC (RFC 4862), MLD (v2) (RFC 3810), NDP (RFC 4861)

Regulatory

- CE:
 - IEC 62368-1:2014
 - EN62368-1:2014 + A11:2017
 - EN55032:2015
 - EN55024:2010 + A1:2015
 - EN 55016-2-1:2009 + A1:2011 + A2:2013
 - EN 55016-2-3:2010 + A1:2010 + A2:2014
 - EN 61000-3-2:2014
 - EN 61000-3-3:2013
- UL/CSA:
 - UL62368-1:2014
 - CSA C22.2 No. 62368-1, Rev. February 17, 2012
- FCC:
 - 47CFR:2011 Part 15, Sub Part B
 - ANSI C63-4:2014
- ACMA:
 - AS/NZS 62368.1:2018
 - AS/NZS CISPR 32:2015

Physical Format

- Modular hot-swap blade
 - AvediaStream c1101 (2 inputs)
 - AvediaStream c1103 (up to 6 inputs)
 - AvediaStream c1210 (up to 20 inputs)

Environment

- Operating: 0 ...+40°C / +32 ... +104°F
- Storage: -20 ...+70°C / -4 ... +158°F
- Operating and storage Relative Humidity: 10-90% (non-condensing)

Dimensions

- L: 275mm x W: 130mm x H: 40mm; weight 0.55kg

Power

- DC 24V: 12.4W Typical, 18.6W Maximum

MTBF

- Calculated to MIL-HDBK-217F, Notice 2: 69334 hours (7.9 years)

In the Box

- AvediaStream g4417-pi, dual DVB-S/S2 gateway with dual CA slots plus Pro:Idiom encryptor
- F-type connector key
- Product Safety Brochure (hard copy)